Robotics **TOOLBOX**

for use with MATLAB (Release 4)

Peter I. Corke August 1996 pic@brb.dmt.csiro.au http://www.brb.dmt.csiro.au/dmt/programs/autom/pic/matlab.html

Peter I. Corke

CSIRO

Division of Manufacturing Technology Preston, AUSTRALIA. 1994

1 Introduction

This Toolbox provides many functions that are useful in robotics and addresses such areas as kinematics, dynamics, and trajectory generation. The Toolbox is useful for simulation as well as analyzing results from experiments with real robots. The Toolbox has been developed and used over the last few years to the point where I rarely write 'C' code anymore for these kinds of tasks. I have used MEX files to read data from an online robot controller (running under VxWorks) via sockets, process it and display it graphically on a workstation computer. It would be feasible, by extension of this communications mechanism, to perform some online robot control functions via MATLAB.

The Toolbox is based on a very general method of representing the kinematics and dynamics of serial-link manipulators by description matrices. These matrices can be created by the user for any serial-link manipulator and a number of examples are provided for well know robots such as the Puma 560 and the Stanford arm. Such matrices provide a concise means of describing a robot model and may facilitate the sharing of robot models across the research community. This would allow simulation results to be compared in a much more meaningful way than is currently done in the literature. The toolbox also provides functions for manipulating datatypes such as vectors, homogeneous transformations and unit-quaternions which are necessary to represent 3-dimensional position and orientation.

The routines are generally written in a straightforward manner which allows for easy understanding at the expense of computational efficiency. If you feel strongly about computational efficiency then you can rewrite the function or create a MEX version.

2 What's new

A number of bug fixes have been included and are described in the file RELEASE. NOTES.

4 MATLAB version issues

The Toolbox home page has moved to

http://www.brb.dmt.csiro.au/dmt/programs/autom/pic/matlab.html

This page will always list the current released version number as well as bug fixes and new code in between major releases.

A Mailing List is now available. To subscribe you send mail to

```
robot-toolbox-request@dmt.csiro.au
```

with the single word "subscribe" in the body of the message. You can send other administrative messages, such as "help", "list", etc. This list is available to all users to discuss bugs and distribute M-files, and I'll use it to notify users of new releases and so on.

3 How to obtain the toolbox

The Robotics Toolbox is freely available from the MathWorks FTP server ftp.mathworks.comin the directory pub/contrib/misc/robot. It is best to download all files in that directory since the Toolbox functions are quite interdependent. The file robot.ps is a comprehensive manual with a tutorial introduction and details of each Toolbox function. A menu-driven demonstration can be invoked by the function rtdemo.

4 MATLAB version issues

The Toolbox works with MATLAB version 4 and has been tested on a Sun with version 4.2c and under MS-Windows version 4.0. The Toolbox does not function under MATLAB v3.x due to the significant changes introduced between MATLAB versions. Problems have also been encountered with the Student edition, particularly the trajectory examples, since these require matrices larger than the limits imposed. Cursory experiments with Octave 1.0¹ under Linux shows up a number of language differences. In particular Octave doesn't like comments

¹Octave is a MATLAB like package that is available for anonymous ftp from ftp://ftp.che.wisc.edu/pub/octave. The current version of Octave is now 1.1.1.

inside matrix definitions or DOS style CRLFs in M files, and does not support the '...' line continuation feature of MATLAB.

5 Acknowledgements

I have corresponded with a great many people via email since the first release of this toolbox. Some have identified bugs and shortcomings in the documentation, and even better, some have provided bug fixes and even new modules. I would particularly like to thank Chris Clover of Iowa State University, Anders Robertsson and Jonas Sonnerfeldt of Lund Institute of Technology, Robert Biro and Gary McMurray of Georgia Institute of Technology, Jean-Luc Nougaret of IRISA, Leon Zlajpah of Jozef Stefan Institute, University of Ljubljana, for their help.

6 Support, use in teaching, bug fixes, etc.

I'm always happy to correspond with people who have found genuine bugs or deficiencies in the Toolbox, or who have suggestions about ways to improve its functionality. However I do draw the line at providing help for people with their assignments and homework!

Many people are using the Toolbox for teaching and this is something that I would encourage. If you plan to duplicate the documentation for class use then every copy must include the front page.

If you want to cite the Toolbox please use

@ARTICLE{Corke96b,

AUTHOR	= {P.I. Corke},
JOURNAL	= {IEEE Robotics and Automation Magazine},
MONTH	= mar,
NUMBER	= {1},
PAGES	= {24-32},
TITLE	= {A Robotics Toolbox for {MATLAB}},
VOLUME	= {3},
YEAR	= {1996}

which is also given in electronic form in the README file.

Robotics Toolbox Release 4

}

1 Tutorial

7 Manipulator kinematics

Kinematics is the study of motion without regard to the forces which cause it. Within kinematics one studies the position, velocity and acceleration, and all higher order derivatives of the position variables. The kinematics of manipulators involves the study of the geometric and time based properties of the motion, and in particular how the various links move with respect to one another and with time.

Typical robots are *serial-link manipulators* comprising a set of bodies, called *links*, in a chain, connected by $joints^2$. Each joint has one degree of freedom, either translational or rotational. For a manipulator with n joints numbered from 1 to n, there are n + 1 links, numbered from 0 to n. Link 0 is the base of the manipulator, generally fixed, and link n carries the end-effector. Joint i connects links i and i - 1.

A link may be considered as a rigid body defining the relationship between two neighbouring joint axes. A link can be specified by two numbers, the *link length* and *link twist*, which define the relative location of the two axes in space. The link parameters for the first and last links are meaningless, but are arbitrarily chosen to be 0. Joints may be described by two parameters. The *link offset* is the distance from one link to the next along the axis of the joint. The *joint angle* is the rotation of one link with respect to the next about the joint axis.

To facilitate describing the location of each link we affix a coordinate frame to it — frame *i* is attached to link *i*. Denavit and Hartenberg[1] proposed a matrix method of systematically assigning coordinate systems to each link of an articulated chain. The axis of revolute joint *i* is aligned with z_{i-1} . The x_{i-1} axis is directed along the normal from z_{i-1} to z_i and for intersecting axes is parallel to $z_{i-1} \times z_i$. The link and joint parameters may be summarized as:

²Parallel link and serial/parallel hybrid structures are possible, though much less common in industrial manipulators.



Figure 1: Different forms of Denavit-Hartenberg notation.

link length a_i		the offset distance between the z_{i-1} and z_i axes along the x_i
		axis;
link twist	α_i	the angle from the z_{i-1} axis to the z_i axis about the x_i axis;
link offset	d_i	the distance from the origin of frame $i-1$ to the x_i axis along
		the z_{i-1} axis;
joint angle	$ heta_i$	the angle between the x_{i-1} and x_i axes about the z_{i-1} axis.

For a revolute axis θ_i is the joint variable and d_i is constant, while for a prismatic joint d_i is variable,

Robotics Toolbox Release 4

1-7

7 Manipulator kinematics

and $heta_i$ is constant. In many of the formulations that follow we use generalized coordinates, q_i , where

$$q_i = \left\{ egin{array}{cc} heta_i & ext{for a revolute joint} \\ d_i & ext{for a prismatic joint} \end{array}
ight.$$

and generalized forces

$$Q_i = \left\{ egin{array}{cc} au_i & \mbox{for a revolute joint} \\ f_i & \mbox{for a prismatic joint} \end{array}
ight.$$

The Denavit-Hartenberg (DH) representation results in a 4x4 homogeneous transformation matrix

$${}^{i-1}\mathbf{A}_{i} = \begin{bmatrix} \cos\theta_{i} & -\sin\theta_{i}\cos\alpha_{i} & \sin\theta_{i}\sin\alpha_{i} & a_{i}\cos\theta_{i} \\ \sin\theta_{i} & \cos\theta_{i}\cos\alpha_{i} & -\cos\theta_{i}\sin\alpha_{i} & a_{i}\sin\theta_{i} \\ 0 & \sin\alpha_{i} & \cos\alpha_{i} & d_{i} \\ 0 & 0 & 0 & 1 \end{bmatrix}$$
(1)

representing each link's coordinate frame with respect to the previous link's coordinate system; that is

$${}^{0}\mathbf{T}_{i} = {}^{0}\mathbf{T}_{i-1} {}^{i-1}\mathbf{A}_{i} \tag{2}$$

where ${}^{0}\mathbf{T}_{i}$ is the homogeneous transformation describing the pose of coordinate frame i with respect to the world coordinate system 0.

Two differing methodologies have been established for assigning coordinate frames, each of which allows some freedom in the actual coordinate frame attachment:

- 1. Frame *i* has its origin along the axis of joint i + 1, as described by Paul[2] and Lee[3, 4].
- 2. Frame *i* has its origin along the axis of joint *i*, and is frequently referred to as 'modified Denavit-Hartenberg' (MDH) form[5]. This form is commonly used in literature dealing with manipulator dynamics. The link transform matrix for this form differs from (1).

Figure 1 shows the notational differences between the two forms. Note that a_i is always the length of link i, but is the displacement between the origins of frame i and frame i + 1 in one convention, and frame i - 1 and frame i in the other³. The Toolbox provides kinematic functions for both of these conventions — those for modified DH parameters are prefixed by 'm'.

³Many papers when tabulating the 'modified' kinematic parameters of manipulators list a_{i-1} and α_{i-1} not a_i and α_i .

7.1 Forward and inverse kinematics

For an n-axis rigid-link manipulator, the *forward kinematic solution* gives the coordinate frame, or pose, of the last link. It is obtained by repeated application of (2)

$${}^{0}\mathbf{T}_{n} = {}^{0}\mathbf{A}_{1}{}^{1}\mathbf{A}_{2}\cdots{}^{n-1}\mathbf{A}_{n} \tag{3}$$

$$= \mathcal{K}(q) \tag{4}$$

which is the product of the coordinate frame transform matrices for each link. The pose of the end-effector has 6 degrees of freedom in Cartesian space, 3 in translation and 3 in rotation, so robot manipulators commonly have 6 joints or degrees of freedom to allow arbitrary end-effector pose. The overall manipulator transform ${}^{0}\mathbf{T}_{n}$ is frequently written as \mathbf{T}_{n} , or \mathbf{T}_{6} for a 6-axis robot. The forward kinematic solution may be computed for any manipulator, irrespective of the number of joints or kinematic structure.

Of more use in manipulator path planning is the *inverse kinematic solution*

$$q = \mathcal{K}^{-1}(\mathbf{T}) \tag{5}$$

which gives the joint angles required to reach the specified end-effector position. In general this solution is non-unique, and for some classes of manipulator no closed-form solution exists. If the manipulator has more than 6 joints it is said to be redundant and the solution for joint angles is under-determined. If no solution can be determined for a particular manipulator pose that configuration is said to be singular. The singularity may be due to an alignment of axes reducing the effective degrees of freedom, or the point T being out of reach.

The manipulator Jacobian matrix, J_{θ} , transforms velocities in joint space to velocities of the endeffector in Cartesian space. For an *n*-axis manipulator the end-effector Cartesian velocity is

$${}^{0}\underline{\dot{x}}_{n} = {}^{0}\mathbf{J}_{\theta}\underline{\dot{q}} \tag{6}$$

$${}^{t_n}\underline{\dot{x}}_n = {}^{t_n}\mathbf{J}_\theta \dot{q} \tag{7}$$

in base or end-effector coordinates respectively and where \underline{x} is the Cartesian velocity represented by a 6-vector. For a 6-axis manipulator the Jacobian is square and provided it is not singular can be inverted to solve for joint rates in terms of end-effector Cartesian rates. The Jacobian will not be invertible at a kinematic singularity, and in practice will be poorly conditioned in the vicinity of the singularity, resulting in high joint rates. A control scheme based on Cartesian rate control

$$\underline{\dot{q}} = {}^{0}\mathbf{J}_{\theta}^{-1} \, {}^{0}\underline{\dot{x}}_{n} \tag{8}$$

was proposed by Whitney[6] and is known as *resolved rate motion control*. For two frames A and B related by ${}^{A}\mathbf{T}_{B} = [\underline{n} \ \underline{o} \ \underline{a} \ \underline{p}]$ the Cartesian velocity in frame A may be transformed to frame B by $B : B \mathbf{I} \ A :$ (0)

$${}^{B}\underline{\dot{x}} = {}^{B}\mathbf{J}_{A} {}^{A}\underline{\dot{x}} \tag{9}$$

8 Manipulator rigid-body dynamics

where the Jacobian is given by Paul[7] as

$${}^{B}\mathbf{J}_{A} = f({}^{A}\mathbf{T}_{B}) = \begin{bmatrix} \underline{[n \ \underline{o} \ \underline{a}]}^{T} & \underline{[p \times \underline{n} \ \underline{p} \times \underline{o} \ \underline{p} \times \underline{a}]^{T} \\ 0 & \underline{[n \ \underline{o} \ \underline{a}]}^{T} \end{bmatrix}$$
(10)

8 Manipulator rigid-body dynamics

Manipulator dynamics is concerned with the equations of motion, the way in which the manipulator moves in response to torques applied by the actuators, or external forces. The history and mathematics of the dynamics of serial-link manipulators is well covered by Paul[2] and Hollerbach[8]. There are two problems related to manipulator dynamics that are important to solve:

- *inverse* dynamics in which the manipulator's equations of motion are solved for given motion to determine the generalized forces, discussed further in Section ??, and
- *direct dynamics* in which the equations of motion are integrated to determine the generalized coordinate response to applied generalized forces discussed further in Section 8.2.

The equations of motion for an *n*-axis manipulator are given by

$$\underline{Q} = \mathbf{M}(\underline{q})\underline{\ddot{q}} + \mathbf{C}(\underline{q},\underline{\dot{q}})\underline{\dot{q}} + \mathbf{F}(\underline{\dot{q}}) + \mathbf{G}(\underline{q})$$
(11)

where

- \underline{q}_{-} is the vector of generalized joint coordinates describing the pose of the manipulator
- $\underline{\dot{q}}$ is the vector of joint velocities;
- $\underline{\ddot{q}}$ is the vector of joint accelerations
- $M \quad \ \ \, \text{is the symmetric joint-space inertia matrix, or manipulator inertia tensor}$
- **C** describes Coriolis and centripetal effects Centripetal torques are proportional to \dot{q}_i^2 , while the Coriolis torques are proportional to $\dot{q}_i \dot{q}_j$
- **F** describes viscous and Coulomb friction and is not generally considered part of the rigid-body dynamics
- $G \quad \ \ is the gravity loading$
- Q is the vector of generalized forces associated with the generalized coordinates q.

The equations may be derived via a number of techniques, including Lagrangian (energy based), Newton-Euler, d'Alembert[3, 9] or Kane's[10] method. The earliest reported work was by Uicker[11] and Kahn[12] using the Lagrangian approach. Due to the enormous computational cost, $O(n^4)$, of this approach it was not possible to compute manipulator torque for real-time control. To achieve real-time performance many approaches were suggested, including table lookup[13] and approximation[14, 15]. The most common approximation was to ignore the velocity-dependent term \mathbf{C} , since accurate positioning and high speed motion are exclusive in typical robot applications.

Method	Multiplications	Additions	For N=6	
			Multiply	Add
Lagrangian[19]	$32\frac{1}{2}n^4 + 86\frac{5}{12}n^3$	$25n^4 + 66\frac{1}{3}n^3$	66,271	51,548
	$+171\frac{1}{4}n^2+53\frac{1}{3}n$	$+129\frac{1}{2}n^2 + 42\frac{1}{3}n$		
	-128	-96		
Recursive NE[19]	150n - 48	131n - 48	852	738
Kane[10]			646	394
Simplified RNE[22]			224	174

Table 1: Comparison of computational costs for inverse dynamics from various sources. The last entry is achieved by symbolic simplification using the software package ARM.

Orin et al.[16] proposed an alternative approach based on the Newton-Euler (NE) equations of rigid-body motion applied to each link. Armstrong[17] then showed how recursion might be applied resulting in O(n) complexity. Luh et al.[18] provided a recursive formulation of the Newton-Euler equations with linear and angular velocities referred to link coordinate frames. They suggested a time improvement from 7.9s for the Lagrangian formulation to 4.5 ms, and thus it became practical to implement 'on-line'. Hollerbach[19] showed how recursion could be applied to the Lagrangian form, and reduced the computation to within a factor of 3 of the recursive NE. Silver[20] showed the equivalence of the recursive Lagrangian and Newton-Euler forms, and that the difference in efficiency is due to the representation of angular velocity.

"Kane's equations" [10] provide another methodology for deriving the equations of motion for a specific manipulator. A number of 'Z' variables are introduced, which while not necessarily of physical significance, lead to a dynamics formulation with low computational burden. Wampler[21] discusses the computational costs of Kane's method in some detail.

The NE and Lagrange forms can be written generally in terms of the Denavit-Hartenberg parameters — however the specific formulations, such as Kane's, can have lower computational cost for the specific manipulator. Whilst the recursive forms are computationally more efficient, the non-recursive forms compute the individual dynamic terms (M, C and G) directly. A comparison of computation costs is given in Table 1.

8.1 Recursive Newton-Euler formulation

The recursive Newton-Euler (RNE) formulation[18] computes the inverse manipulator dynamics, that is, the joint torques required for a given set of joint angles, velocities and accelerations. The forward recursion propagates kinematic information — such as angular velocities, angular acceler-

1–11

8 Manipulator rigid-body dynamics



Figure 2: Notation used for inverse dynamics, based on standard Denavit-Hartenberg notation.

ations, linear accelerations — from the base reference frame (inertial frame) to the end-effector. The backward recursion propagates the forces and moments exerted on each link from the end-effector of the manipulator to the base reference frame⁴. Figure 2 shows the variables involved in the computation for one link.

The notation of Hollerbach[19] and Walker and Orin [23] will be used in which the left superscript indicates the reference coordinate frame for the variable. The notation of Luh et al.[18] and later Lee[4, 3] is considerably less clear.

Outward recursion, $1 \le i \le n$.

If axis i + 1 is rotational

$${}^{i+1}\underline{\omega}_{i+1} = {}^{i+1}\mathbf{R}_i \left({}^{i}\underline{\omega}_i + \underline{z}_0 \underline{\dot{q}}_{i+1} \right)$$
(12)

$${}^{i+1}\underline{\dot{\omega}}_{i+1} = {}^{i+1}\mathbf{R}_i \left\{ {}^{i}\underline{\dot{\omega}}_i + \underline{z}_0 \underline{\ddot{q}}_{i+1} + {}^{i}\underline{\omega}_i \times \left(\underline{z}_0 \underline{\dot{q}}_{i+1} \right) \right\}$$
(13)

$${}^{i+1}\underline{\underline{\nu}}_{i+1} = {}^{i+1}\underline{\underline{\omega}}_{i+1} \times {}^{i+1}\underline{\underline{p}}_{i+1}^* + {}^{i+1}\mathbf{R}_i{}^i\underline{\underline{\nu}}_i$$

$$(14)$$

$$\overset{i+1}{\underline{\upsilon}}_{i+1} = \overset{i+1}{\underline{\omega}}_{i+1} \times \overset{i+1}{\underline{p}}_{i+1}^* + \overset{i+1}{\underline{\omega}}_{i+1} \times \left\{ \overset{i+1}{\underline{\omega}}_{i+1} \times \overset{i+1}{\underline{p}}_{i+1}^* \right\} + \overset{i+1}{\mathbf{R}}_i^{\ i} \underbrace{\dot{\underline{\upsilon}}_i}_{i} \tag{15}$$
If axis $i+1$ is translational

$${}^{i+1}\underline{\omega}_{i+1} = {}^{i+1}\mathbf{R}_i{}^i\underline{\omega}_i \tag{16}$$

⁴It should be noted that using MDH notation with its different axis assignment conventions the Newton Euler formulation is expressed differently[5].

$${}^{i+1}\underline{\dot{\omega}}_{i+1} = {}^{i+1}\mathbf{R}_i{}^i\underline{\dot{\omega}}_i \tag{17}$$

$${}^{i+1}\underline{v}_{i+1} = {}^{i+1}\mathbf{R}_i \left(\underline{z}_0 \underline{\dot{q}}_{i+1} + {}^i \underline{v}_i \right) + {}^{i+1}\underline{\omega}_{i+1} \times {}^{i+1}\underline{p}_{i+1}^*$$
(18)

$$\overset{i+1}{\underline{\upsilon}}_{i+1} = \overset{i+1}{\mathbf{R}}_{i} \left(\underline{z}_{0} \underline{\ddot{q}}_{i+1} + \overset{i}{\underline{\upsilon}}_{i} \right) + \overset{i+1}{\underline{\omega}}_{i+1} \times \overset{i+1}{\underline{p}}_{i+1}^{*} + 2 \overset{i+1}{\underline{\omega}}_{i+1} \times \left(\overset{i+1}{\mathbf{R}}_{i\underline{z}_{0}} \underline{\dot{q}}_{i+1} \right)$$

$$+ \overset{i+1}{\underline{\omega}}_{i+1} \times \left(\overset{i+1}{\underline{\omega}}_{i+1} \times \overset{i+1}{\underline{p}}_{i+1}^{*} \right)$$

$$(19)$$

$${}^{i}\underline{\dot{v}}_{i} = {}^{i}\underline{\dot{\omega}}_{i} \times \underline{s}_{i} + {}^{i}\underline{\omega}_{i} \times \{{}^{i}\underline{\omega}_{i} \times \underline{s}_{i}\} + {}^{i}\underline{\dot{v}}_{i}$$
(20)

$$\underline{F}_i = m_i^i \underline{\underline{v}}_i \tag{21}$$

Inward recursion, $n \ge i \ge 1$.

$${}^{i}\underline{f}_{i} = {}^{i}\mathbf{R}_{i+1}{}^{i+1}\underline{f}_{i+1} + {}^{i}\underline{F}_{i}$$

$${}^{i}\underline{n}_{i} = {}^{i}\mathbf{R}_{i+1} \left\{ {}^{i+1}\underline{n}_{i+1} + \left({}^{i+1}\mathbf{R}_{i}{}^{i}\underline{p}_{i}^{*} \right) \times {}^{ii+1}\underline{f}_{i+1} \right\} + \left({}^{i}\underline{p}_{i}^{*} + \underline{s}_{i} \right) \times {}^{i}\underline{F}_{i} + {}^{i}\underline{N}_{i}$$

$$(23)$$

$$\underline{Q}_{i} = \begin{cases} \left(\frac{i}{\underline{n}_{i}}\right)^{T} \left(^{i}\mathbf{R}_{i+1}\underline{z}_{0}\right) & \text{if link } i+1 \text{ is rotational} \\ \left(\frac{i}{\underline{f}_{i}}\right)^{T} \left(^{i}\mathbf{R}_{i+1}\underline{z}_{0}\right) & \text{if link } i+1 \text{ is translational} \end{cases}$$
(25)

where

i	is the link index, in the range 1 to n
\mathbf{J}_i	is the moment of inertia of link i about its COM
\underline{s}_i	is the position vector of the COM of link \boldsymbol{i} with respect to frame \boldsymbol{i}
$\underline{\omega}_i$	is the angular velocity of link i
$\dot{\omega}_i$	is the angular acceleration of link \dot{i}
\underline{v}_i	is the linear velocity of frame i
\underline{v}_i	is the linear acceleration of frame \dot{i}
\overline{v}_i	is the linear velocity of the COM of link \dot{i}
\overline{v}_i	is the linear acceleration of the COM of link \boldsymbol{i}
\underline{n}_i	is the moment exerted on link i by link $i-1$
f_{i}	is the force exerted on link i by link $i-1$
\overline{N}_i	is the total moment at the COM of link i
\underline{F}_i	is the total force at the COM of link \boldsymbol{i}
Q_{i}	is the force or torque exerted by the actuator at joint \boldsymbol{i}

- is the force exerted on link $i \; {\rm by} \; {\rm link} \; i-1$
- is the total moment at the COM of link $\ensuremath{\boldsymbol{i}}$
- is the total force at the COM of link \boldsymbol{i}
- is the force or torque exerted by the actuator at joint \boldsymbol{i}

8 Manipulator rigid-body dynamics

 $i^{i-1}\mathbf{R}_i$ is the orthonormal rotation matrix defining frame i orientation with respect to frame i-1. It is the upper 3×3 portion of the link transform matrix given in (1).

$${}^{i-1}\mathbf{R}_{i} = \begin{bmatrix} \cos\theta_{i} & -\cos\alpha_{i}\sin\theta_{i} & \sin\alpha_{i}\sin\theta_{i} \\ \sin\theta_{i} & \cos\alpha_{i}\cos\theta_{i} & -\sin\alpha_{i}\cos\theta_{i} \\ 0 & \sin\alpha_{i} & \cos\alpha_{i} \end{bmatrix}$$
(26)

$${}^{i}\mathbf{R}_{i-1} = ({}^{i-1}\mathbf{R}_{i})^{-1} = ({}^{i-1}\mathbf{R}_{i})^{T}$$
 (27)

 ${}^{i}p_{i}^{*}$ is the displacement from the origin of frame i-1 to frame i with respect to frame i.

$${}^{i}\underline{p}_{i}^{*} = \begin{bmatrix} a_{i} \\ d_{i}\sin\alpha_{i} \\ d_{i}\cos\alpha_{i} \end{bmatrix}$$
(28)

It is the negative translational part of $({}^{i-1}\mathbf{A}_i)^{-1}$. \underline{z}_0 is a unit vector in Z direction, $\underline{z}_0 = [0 \ 0 \ 1]$

Note that the COM linear velocity given by equation (14) or (18) does not need to be computed since no other expression depends upon it. Boundary conditions are used to introduce the effect of gravity by setting the acceleration of the base link

$$\dot{v}_0 = -\underline{g} \tag{29}$$

where \underline{g} is the gravity vector in the reference coordinate frame, generally acting in the negative Z direction, downward. Base velocity is generally zero

$$v_0 = 0 \tag{30}$$

$$\omega_0 = 0 \tag{31}$$

$$\dot{\omega}_0 = 0 \tag{32}$$

At this stage the Toolbox only provides an implementation of this algorithm using the standard Denavit-Hartenberg conventions.

8.2 Direct dynamics

Equation (11) may be used to compute the so-called inverse dynamics, that is, actuator torque as a function of manipulator state and is useful for on-line control. For simulation the direct, integral or *forward dynamic* formulation is required giving joint motion in terms of input torques.

Walker and Orin[23] describe several methods for computing the forward dynamics, and all make use of an existing inverse dynamics solution. Using the RNE algorithm for inverse dynamics, the computational complexity of the forward dynamics using 'Method 1' is $O(n^3)$ for an n-axis manipulator. Their other methods are increasingly more sophisticated but reduce the computational cost, though still $O(n^3)$. Featherstone[24] has described the "articulated-body method" for O(n)computation of forward dynamics, however for n < 9 it is more expensive than the approach of Walker and Orin. Another O(n) approach for forward dynamics has been described by Lathrop[25].

8.3 Rigid-body inertial parameters

Accurate model-based dynamic control of a manipulator requires knowledge of the rigid-body inertial parameters. Each link has ten independent inertial parameters:

- link mass, m_i ;
- three first moments, which may be expressed as the COM location, \underline{s}_i , with respect to some datum on the link or as a moment $\underline{S}_i = m_i \underline{s}_i$;
- six second moments, which represent the inertia of the link about a given axis, typically through the COM. The second moments may be expressed in matrix or tensor form as

$$\mathbf{J} = \begin{bmatrix} J_{xx} & J_{xy} & J_{xz} \\ J_{xy} & J_{yy} & J_{yz} \\ J_{xz} & J_{yz} & J_{zz} \end{bmatrix}$$
(33)

where the diagonal elements are the moments of inertia, and the off-diagonals are products of inertia. Only six of these nine elements are unique: three moments and three products of inertia.

For any point in a rigid-body there is one set of axes known as the *principal axes of inertia* for which the off-diagonal terms, or products, are zero. These axes are given by the eigenvectors of the inertia matrix (33) and the eigenvalues are the principal moments of inertia. Frequently the products of inertia of the robot links are zero due to symmetry.

A 6-axis manipulator rigid-body dynamic model thus entails 60 inertial parameters. There may be additional parameters per joint due to friction and motor armature inertia. Clearly, establishing numeric values for this number of parameters is a difficult task. Many parameters cannot be measured without dismantling the robot and performing careful experiments, though this approach was used by Armstrong et al.[26]. Most parameters could be derived from CAD models of the robots, but this information is often considered proprietary and not made available to researchers.

References

- R. S. Hartenberg and J. Denavit, "A kinematic notation for lower pair mechanisms based on matrices," *Journal of Applied Mechanics*, vol. 77, pp. 215–221, June 1955.
- [2] R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.
- [3] K. S. Fu, R. C. Gonzalez, and C. S. G. Lee, Robotics. Control, Sensing, Vision and Intelligence. McGraw-Hill, 1987.
- [4] C. S. G. Lee, "Robot arm kinematics, dynamics and control," *IEEE Computer*, vol. 15, pp. 62–80, Dec. 1982.
- [5] J. J. Craig, Introduction to Robotics. Addison Wesley, second ed., 1989.
- [6] D. Whitney and D. M. Gorinevskii, "The mathematics of coordinated control of prosthetic arms and manipulators," ASME Journal of Dynamic Systems, Measurement and Control, vol. 20, no. 4, pp. 303–309, 1972.
- [7] R. P. Paul, B. Shimano, and G. E. Mayer, "Kinematic control equations for simple manipulators," IEEE Trans. Syst. Man Cybern., vol. 11, pp. 449–455, June 1981.
- [8] J. M. Hollerbach, "Dynamics," in *Robot Motion Planning and Control* (M. Brady, J. M. Hollerbach, T. L. Johnson, T. Lozano-Perez, and M. T. Mason, eds.), pp. 51–71, MIT, 1982.
- [9] C. S. G. Lee, B. Lee, and R. Nigham, "Development of the generalized D'Alembert equations of motion for mechanical manipulators," in *Proc. 22nd CDC*, (San Antonio, Texas), pp. 1205– 1210, 1983.
- [10] T. Kane and D. Levinson, "The use of Kane's dynamical equations in robotics," Int. J. Robot. Res., vol. 2, pp. 3–21, Fall 1983.
- [11] J. Uicker, On the Dynamic Analysis of Spatial Linkages Using 4 by 4 Matrices. PhD thesis, Dept. Mechanical Engineering and Astronautical Sciences, NorthWestern University, 1965.
- [12] M. Kahn, "The near-minimum time control of open-loop articulated kinematic linkages," Tech. Rep. AIM-106, Stanford University, 1969.
- [13] M. H. Raibert and B. K. P. Horn, "Manipulator control using the configuration space method," *The Industrial Robot*, pp. 69–73, June 1978.
- [14] A. Bejczy, "Robot arm dynamics and control," Tech. Rep. NASA-CR-136935, NASA JPL, Feb. 1974.

- [15] R. Paul, "Modelling, trajectory calculation and servoing of a computer controlled arm," Tech. Rep. AIM-177, Stanford University, Artificial Intelligence Laboratory, 1972.
- [16] D. Orin, R. McGhee, M. Vukobratovic, and G. Hartoch, "Kinematics and kinetic analysis of open-chain linkages utilizing Newton-Euler methods," *Mathematical Biosciences*. An International Journal, vol. 43, pp. 107–130, Feb. 1979.
- [17] W. Armstrong, "Recursive solution to the equations of motion of an n-link manipulator," in Proc. 5th World Congress on Theory of Machines and Mechanisms, (Montreal), pp. 1343–1346, July 1979.
- [18] J. Y. S. Luh, M. W. Walker, and R. P. C. Paul, "On-line computational scheme for mechanical manipulators," ASME Journal of Dynamic Systems, Measurement and Control, vol. 102, pp. 69–76, 1980.
- [19] J. Hollerbach, "A recursive Lagrangian formulation of manipulator dynamics and a comparative study of dynamics formulation complexity," *IEEE Trans. Syst. Man Cybern.*, vol. SMC-10, pp. 730–736, Nov. 1980.
- [20] W. M. Silver, "On the equivalance of Lagrangian and Newton-Euler dynamics for manipulators," *Int. J. Robot. Res.*, vol. 1, pp. 60–70, Summer 1982.
- [21] C. Wampler, Computer Methods in Manipulator Kinematics, Dynamics, and Control: a Comparative Study. PhD thesis, Stanford University, 1985.
- [22] J. J. Murray, Computational Robot Dynamics. PhD thesis, Carnegie-Mellon University, 1984.
- [23] M. W. Walker and D. E. Orin, "Efficient dynamic computer simulation of robotic mechanisms," ASME Journal of Dynamic Systems, Measurement and Control, vol. 104, pp. 205– 211, 1982.
- [24] R. Featherstone, Robot Dynamics Algorithms. Kluwer Academic Publishers, 1987.
- [25] R. Lathrop, "Constrained (closed-loop) robot simulation by local constraint propogation.," in Proc. IEEE Int. Conf. Robotics and Automation, pp. 689–694, 1986.
- [26] B. Armstrong, O. Khatib, and J. Burdick, "The explicit dynamic model and inertial parameters of the Puma 560 arm," in *Proc. IEEE Int. Conf. Robotics and Automation*, vol. 1, (Washington, USA), pp. 510–18, 1986.

REFERENCES

1–18

2 Reference

Symbol	Dimensions	Description
dh	$n \times 5$	manipulator kinematic description matrix
dyn	$n \times 20$	manipulator kinematic and dynamic de-
		scription matrix
q	$1 \times n$	joint coordinate vector
q	$m \times n$	<i>m</i> -point joint coordinate trajectory
qd	$1 \times n$	joint velocity vector
qd	$m \times n$	<i>m</i> -point joint velocity trajectory
qdd	$1 \times n$	joint acceleration vector
qdd	$m \times n$	<i>m</i> -point joint acceleration trajectory
Т	4×4	homogeneous transform
Т	$m \times 16$	<i>m</i> -point homogeneous transform trajectory
Q	1×4	unit-quaternion
М	1×6	vector with elements of 0 or 1 corresponding
		to Cartesian DOF along X, Y, Z and around
		X, Y, Z. 1 if that Cartesian DOF belongs to
		the task space, else 0.
v	3×1	Cartesian vector
t	$m \times 1$	time vector
d	6×1	differential motion vector

For an n-axis manipulator the following matrix naming and dimensional conventions apply.

A trajectory is represented by a matrix in which each row corresponds to one of *m* time steps. For a joint coordinate, velocity or acceleration trajectory the columns correspond to the robot axes. Things are a little more complicated for homogeneous transform trajectories since MATLAB does not (yet) support 3-dimensional matrices. The approach used in this Toolbox is that each row is a homogeneous transform that has been 'flattened' using the (:) operator. Each row can be restored to a 4×4 matrix by using the reshape function.

Unless indicated by '(modified Denavit-Hartenberg)' all functions work with

standard Denavit-Hartenberg parameters.

Homogeneous Transforms			
eul2tr	Euler angle to homogeneous transform		
oa2tr	orientation and approach vector to homogeneous		
	transform		
rotx	homogeneous transform for rotation about X-axis		
roty	homogeneous transform for rotation about Y-axis		
rotz	homogeneous transform for rotation about Z-axis		
rpy2tr	Roll/pitch/yaw angles to homogeneous transform		
tr2eul	homogeneous transform to Euler angles		
tr2rpy	homogeneous transform to roll/pitch/yaw angles		

Quaternions			
q2tr	quaternion to homogeneous transform		
qinv	inverse of quaternion		
qnorm	normalize a quaternion		
qqmul	multiply (compound) quaternions		
qvmul	multiply vector by quaternion		
qinterp	interpolate quaternions		
tr2q	homogeneous transform to unit-quaternion		

Kinematics			
dh	Denavit-Hartenberg conventions		
diff2tr	differential motion vector to transform		
fkine	compute forward kinematics		
ikine	compute inverse kinematics		
ikine560	compute inverse kinematics for Puma 560 like arm		
jacob0	compute Jacobian in base coordinate frame		
jacobn	compute Jacobian in end-effector coordinate frame		
linktrans	compute a link transform homogeneous transform		
mdh	modified Denavit-Hartenberg conventions		
mfkine	nfkine compute forward kinematics (modified Denay		
	Hartenberg)		
mlinktrans	compute a link transform homogeneous trans-		
	form(modified Denavit-Hartenberg)		
tr2diff	homogeneous transform to differential motion vec-		
	tor		
tr2jac	homogeneous transform to Jacobian		

	Dynamics		
accel	compute forward dynamics		
cinertia	compute Cartesian manipulator inertia matrix		
coriolis	compute centripetal/coriolis torque		
dyn	dynamics conventions		
friction	joint friction		
gravload	compute gravity loading		
inertia	compute manipulator inertia matrix		
itorque	compute inertia torque		
mdyn	dynamics conventions (modified Denavit-		
	Hartenberg)		
mrne	inverse dynamics (modified Denavit-Hartenberg)		
rne	inverse dynamics		

Manipulator Models			
puma560	Puma 560 data		
puma560akb	Puma 560 data (modified Denavit-Hartenberg)		
stanford	Stanford arm data		

Trajectory Generation			
ctraj	Cartesian trajectory		
drivepar	Cartesian trajectory parameters		
jtraj	joint space trajectory		
trinterp	interpolate homogeneous transforms		
ttg	extract homogeneous transform from Cartesian tra-		
	jectory matrix		

	Graphics	
plotbot	animate robot	

	Other	
manipblty	compute manipulability	
rtdemo	toolbox demonstration	
unit	unitize a vector	

accel

Purpose	Compute manipulator forward dynamics
Synopsis	qdd = accel(dyn, q, qd, torque)
Description	Returns a vector of joint accelerations that result from applying the actuator torque to the manipulator with joint coordinates q and velocities qd .
	Uses the method 1 of Walker and Orin to compute the forward dynamics. This form is useful for simulation of manipulator dynamics, in conjunction with a numerical integration function.
See Also	rne, dyn, fdyn, ode45
References	M. W. Walker and D. E. Orin. Efficient dynamic computer simulation of robotic mechanisms. ASME Journal of Dynamic Systems, Measurement and Control, 104:205–211, 1982.

cinertia

Compute the Cartesian manipulator inertia matrix
cinertia(dyn, q) cinertia(dyn, q, M)
cinertia computes the Cartesian, or operational space, inertia matrix. dyn describes the manipulator dynamics and kinematics, and $\tt q$ is an n-element vector of joint coordinates.
For the case of a manipulator with fewer than 6 DOF the task space cannot include all Cartesian DOF. The 6-element weighting vector, M, whose elements are 0 for those Cartesian DOF that belong to the task space, and 1 otherwise. The elements correspond to translation along the X-, Y- and Z-axes and rotation about the X-, Y- and Z-axes. For example, a 5-axis manipulator may be incapable of independantly controlling rotation about the end-effector's Z-axis for which M = $[1 \ 1 \ 1 \ 1 \ 0]$.
The Cartesian inertia matrix is calculated from the joint-space inertia matrix by $\mathbf{M}(\underline{x}) = \mathbf{J}(\underline{q})^{-T}\mathbf{M}(\underline{q})\mathbf{J}(\underline{q})^{-1}$
and relates Cartesian force/torque to Cartesian acceleration
$\underline{F} = \mathbf{M}(\underline{x})\underline{\ddot{x}}$
inertia, dyn, rne
O. Khatib, "A unified approach for motion and force control of robot manipulators: the operational space formulation," <i>IEEE Trans. Robot. Autom.</i> , vol. 3, pp. 43–53, Feb. 1987.

coriolis

Purpose	Compute the manipulator Coriolis/centripetal torque components
Synopsis	tau_c = coriolis(dyn, q, qd)
Description	coriolis returns the joint torques due to rigid-body Coriolis and centripetal effects for the specified joint state ${\rm q}$ and velocity ${\rm qd.}~{\rm dyn}$ describes the manipulator dynamics and kinematics.
	If q and qd are row vectors, tau_c is a row vector of joint torques. If q and qd are matrices, each row is interpreted as a joint state vector, and tau_c is a matrix each row being the corresponding joint torques.
Algorithm	Evaluated from the equations of motion, using $\tt rne,$ with joint acceleration and gravitational acceleration set to zero,
	$\underline{ au} = \mathbf{C}(\underline{q}, \underline{\dot{q}}) \underline{\dot{q}}$
Limitations	If dyn includes joint friction, then friction torque will added to the rigid-body velocity torques returned by $\tt coriolis.$
See Also	dyn, rne, itorque, gravload
References	M. W. Walker and D. E. Orin. Efficient dynamic computer simulation of robotic mechanisms. ASME Journal of Dynamic Systems, Measurement and Control, 104:205–211, 1982.

cross

Purpose	Vector cross product
Synopsis	v = cross(v1, v2)
Description	Returns the vector cross product v1 \times v2.
	Note that this function is no longer provided with the Toolbox since it is now part of the core MATLAB toolboxe (datafun/cross.m).

ctraj

Purpose	Compute a Cartesian trajectory between two points
Synopsis	TC = ctraj(T0, T1, n) TC = ctraj(T0, T1, t)
Description	ctraj returns a Cartesian trajectory (straight line motion) TC from the point represented by homogeneous transform TO to T1. The number of points along the path is n or the length of the given time vector t.
	Each row of $\ensuremath{\mbox{\tiny TC}}$ represents one time step and is a 'flattened' homogeneous transform which can be restored by
	<pre>Ti = reshape(TC(i,:),4,4) , or Ti = ttg(TC, i)</pre>
See Also	trinterp, drivepar, transl, ttg
References	R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

dh

Purpose	Matrix represe	entation of	f manipulator kinematics
Description	A dh matrix describes the kinematics of a manipulator in a general way using the standard Denavit-Hartenberg conventions. Each row represents one link of the manipulator and the columns are assigned according to the following table.		
	Column	Symbol	Description
	1	α_i	link twist angle
	2	A_i	link length
	3	θ_{i}	link rotation angle
	4	D_i	link offset distance
	5	σ_i	joint type; 0 for revolute, non-zero for prismatic
	If the last colu is all-revolute.	mn is not For an n-	given, toolbox functions assume that the manipulator axis manipulator dh is an $n \times 4$ or $n \times 5$ matrix.
	The first 5 colu used anywhere ignored.	mns of a dy e that a di	yn matrix contain the kinematic parameters and maybe n kinematic matrix is required — the dynamic data is
	Lengths A_i and the units in wh angles are in ra	l D_i may l iich homog adians.	be expressed in any unit, and this choice will flow on to geneous transforms and Jacobians are represented. All
See Also	dyn,puma560,s	stanford,n	ndh
References	R. P. Paul, <i>Rob</i> bridge, Massac	ot Manipu husetts: N	lators: Mathematics, Programming, and Control. Cam- MIT Press, 1981.

diff2tr

Purpose	Convert a differential motion vector to a homogeneous transform
Synopsis	T = diff2tr(d)
Description	Returns a homogeneous transform representing a differential translation and rotation.
Algorithm	For a differential motion $\Delta = [d_x \ d_y \ d_z \ \delta_x \ \delta_y \ \delta_z]$ the corresponding homogeneous transform is $\Delta = \begin{bmatrix} 0 & -\delta_z & \delta_y & d_x \\ \delta_z & 0 & -\delta_x & d_y \\ -\delta_y & \delta_x & 0 & d_z \\ 0 & 0 & 0 & 0 \end{bmatrix}$ Note that the rotational submatrix is skew-symmetric.
See Also	tr2diff
References	R. P. Paul. Robot Manipulators: Mathematics, Programming, and Control. MIT Press, Cambridge, Massachusetts, 1981.

drivepar

Purpose	Compute Cartesian path drive parameters
Synopsis	dp = drivepar(T0, T1)
Description	drivepar returns a vector which represents the 'difference' between homogeneous transform TO and T1. This is most frequently used in planning a Cartesian path between homogeneous transform TO and T1 and dp would be passed to trinterp.
See Also	ctraj, trinterp
References	R. P. Paul, <i>Robot Manipulators: Mathematics, Programming, and Control.</i> Cambridge, Massachusetts: MIT Press, 1981.

dyn

Purpose Matrix representation of manipulator kinematics and dynamics

Description A dyn matrix describes the kinematics and dynamics of a manipulator in a general way using the standard Denavit-Hartenberg conventions. Each row represents one link of the manipulator and the columns are assigned according to the following table.

Column	Symbol	Description
1	α	link twist angle
2	Α	link length
3	heta	link rotation angle
4	D	link offset distance
5	σ	joint type; 0 for revolute, non-zero for prismatic
6	mass	mass of the link
7	rx	link COG with respect to the link coordinate frame
8	ry	
9	rz	
10	Ixx	elements of link inertia tensor about the link COG
11	Iyy	
12	Izz	
13	Ixy	
14	Iyz	
15	Ixz	
16	Jm	armature inertia
17	G	reduction gear ratio; joint speed/link speed
18	В	viscous friction, motor referred
19	Tc+	coulomb friction (positive rotation), motor referred
20	Tc-	coulomb friction (negative rotation), motor referred

For an n-axis manipulator, dyn is an $n \times 20$ matrix. The first 5 columns of a dyn matrix contain the kinematic parameters and maybe used anywhere that a dh kinematic matrix is required — the dynamic data is ignored.

All angles are in radians. The choice of all other units is up to the user, and this

dyn

dh

choice will flow on to the units in which homogeneous transforms, Jacobians, inertias and torques are represented.

See Also

eul2tr

Purpose	Convert Euler angles to a homogeneous transform
Synopsis	T = eul2tr([r p y]) T = eul2tr(r,p,y)
Description	eul2tr returns a homogeneous transformation for the specified Euler angles in radians. These correspond to rotations about the Z, X, and Z axes respectively.
See Also	tr2eul, rpy2tr
References	R. P. Paul , <i>Robot Manipulators: Mathematics, Programming, and Control.</i> Cambridge, Massachusetts: MIT Press, 1981.

fdyn

Purpose	Integrate forward dynamics
Synopsis	<pre>[t q qd] = fdyn(dyn, t0, t1) [t q qd] = fdyn(dyn, t0, t1, torqfun) [t q qd] = fdyn(dyn, t0, t1, torqfun, q0, qd0)</pre>
Description	fdyn integrates the manipulator equations of motion over the time interval to to t1 using MATLAB's ode45 numerical integration function. It returns a time vector t, and matrices of manipulator joint state q and joint velocities qd. These matrices have one row per time step and one column per joint.
	Actuator torque may be specified by a user function
	tau = torqfun(t, x)
	where t is the current time, and $x = [q; qd]$ is a 2n-element column vector of manipulator joint coordinate and velocity state. Typically this would be used to implement some axis control scheme. If torqfun is not specified then zero torque is applied to the manipulator.
	Initial joint coordinates and velocities may be specified by the optional arguments $_{\rm q0}$ and $_{\rm qd0}$ respectively.
Algorithm	The joint acceleration is a function of joint coordinate and velocity given by
	$\underline{q} = \mathbf{M}(\underline{q}) - \{\underline{\tau} - \mathbf{C}(\underline{q}, \underline{q})\underline{q} - \mathbf{G}(\underline{q}) - \mathbf{F}(\underline{q})\}$
Example	The following example shows how $fdyn()$ can be used to simulate a robot and its controller. The manipulator is a Puma 560 with simple proportional and derivative controller. The simulation results are shown in the figure. Note that high gains are required on joints 2 and 3 in order to counter the significant disturbance torque due to gravity.

```
fdyn
```

```
>> puma560  % load Puma parameters
>> t = [0:.056:5]';  % time vector
>> q_dmd = jtraj(qz, qr,t);  % create a path
>> qt = [t q_dmd];
>> Pgain = [20 100 20 5 5 5];  % set gains
>> Dgain = [-5 -10 -2 0 0 0];
>> global qt Pgain Dgain
>> [tsim,q,qd] = fdyn(p560, 0, 5, 'taufunc')
```

and the invoked function is

```
%
%
         taufunc.m
%
\% user written function to compute joint torque as a function
\% of joint error. The desired path is passed in via the global
\% matrix qt. The controller implemented is PD with the proportional
\% and derivative gains given by the global variables Pgain and Dgain
% respectively.
%
function tau = taufunc(t, x)
    global
                  Pgain Dgain qt;
    q = x(1:6)'; qd = x(7:12)';
                                    % extract state variables
    if t > qt(length(qt),1),
                                    % keep time in range
        t = qt(length(qt), 1);
    end
    \% interpolate demanded angles for this time
    q_dmd = interp1(qt(:,1), qt(:,2:7), t);
    % compute error and joint torque
    e = q_dmd - q;
    tau = e * diag(Pgain) + qd * diag(Dgain)
```



Results of fdyn() example. Simulated path shown as solid, and reference path as dashed. accel, rne, dyn, ode45 $\,$

References M. W. Walker and D. E. Orin. Efficient dynamic computer simulation of robotic mechanisms. ASME Journal of Dynamic Systems, Measurement and Control, 104:205-211, 1982.

Robotics Toolbox Release 4



See Also
fkine

Purpose	Forward robot kinematics for serial link manipulator
Synopsis	T = fkine(dh, q)
Description	fkine computes forward kinematics for the joint coordinate q. dh describes the manipu- lator kinematics in standard Denavit-Hartenberg notation.
	If q is a vector it is interpreted as the generalized joint coordinates, and fkine returns a homogeneous transformation for the final link of the manipulator. If q is a matrix each row is interpreted as as a joint state vector, and T is a matrix in which each row is the 'flattened' homogeneous transform for the the corresponding row in q. The 'flattened' transform can be restored by
	<pre>Ti = reshape(T(i,:),4,4) , or Ti = ttg(T, i)</pre>
Cautionary	Note that the dimensional units for the last column of the T matrix will be the same as the dimensional units used in the dh matrix. The units used in the dh matrix can be whatever you choose (metres, inches, cubits or furlongs) but the choice will affect the numerical value of the elements in the last column of T. The Toolbox definitions puma560 and stanford all use SI units with dimensions in metres.
See Also	dh,linktran, mfkine
References	R. P. Paul. Robot Manipulators: Mathematics, Programming, and Control. MIT Press, Cambridge, Massachusetts, 1981.

1982.

friction

Purpose	Compute joint friction torque
Synopsis	$tau_f = friction(dyn, qd)$
Description	friction computes the joint friction torque based on friction parameter data in dyn. Friction is a function only of joint velocity qd.
Algorithm	The friction model is a fairly standard one comprising viscous friction and direction dependent Coulomb friction $F_i(t) = \begin{cases} B_i + \tau_i^- \dot{q} , & \dot{\theta} < 0 \\ B_i + \tau_i^+ \dot{q} , & \dot{\theta} > 0 \end{cases}$
See Also	dyn,coriolis
References	M. W. Walker and D. E. Orin. Efficient dynamic computer simulation of robotic mech- anisms. ASME Journal of Dynamic Systems, Measurement and Control, 104:205–211,

1982.

gravload

Purpose	Compute the manipulator gravity torque components
Synopsis	tau_g = gravload(dyn, q) tau_g = gravload(dyn, q, grav)
Description	gravload computes the joint torque due to gravity for the manipulator in pose q. If q is a row vector, tau_g returns a row vector of joint torques. If q is a matrix each row is interpreted as as a joint state vector, and tau_g is a matrix in which each row is the gravity torque for the the corresponding row in q. grav allows an arbitrary gravity vector to override the default of grav = $[0; 0; 9.81]$.
See Also	dyn, rne, itorque, coriolis
References	M. W. Walker and D. E. Orin. Efficient dynamic computer simulation of robotic mech- anisms. ASME Journal of Dynamic Systems, Measurement and Control, 104:205–211,

ikine

Purpose	Inverse manipulator kinematics
Synopsis	<pre>q = ikine(dh, T) q = ikine(dh, T, q0) q = ikine(dh, T, q0, M)</pre>
Description	ikine returns the joint coordinates corresponding to the end-effector homogeneous trans- form T . Note that the inverse kinematic solution is generally not unique, and depends on the initial value q0 (which defaults to 0).
	If T is a homogeneous transform then a row vector of joint coordinates is returned. If T is a homogeneous transform trajectory then q will be a matrix in which each row is the joint coordinates for the corresponding row of T. The initial estimate of q for each time step is taken as the solution from the previous time step. The estimate for the first step in $q0$ if this is given else 0.
	For the case of a manipulator with fewer than 6 DOF it is not possible for the end- effector to satisfy the end-effector pose specified by an arbitrary homogeneous transform. This typically leads to non-convergence in ikine. A solution is to specify a 6-element weighting vector, M, whose elements are 0 for those Cartesian DOF that are unconstrained and 1 otherwise. The elements correspond to translation along the X-, Y- and Z-axes and rotation about the X-, Y- and Z-axes. For example, a 5-axis manipulator may be incapable of independantly controlling rotation about the end-effector's Z-axis. In this case $M = [1$ $1 \ 1 \ 1 \ 1 \ 0]$ would enable a solution in which the end-effector adopted the pose T <i>except</i> for the end-effector rotation. The number of non-zero elements should equal the number of robot DOF.
Algorithm	The solution is computed iteratively using the pseudo-inverse of the manipulator Jacobian.
Cautionary	Such a solution is completely general, though much less efficient than specific inverse kinematic solutions derived symbolically.
	Robotics Toolbox Release 4

This approach allows a solution to obtained at a singularity, but the joint coordinates within the null space are arbitrarily assigned.

Note that the dimensional units used for the last column of the T matrix must agree with the dimensional units used in the dh matrix. These units can be whatever you choose (metres, inches, cubits or furlongs) but they must be consistent. The Toolbox definitions puma560 and stanford all use SI units with dimensions in metres.

- See Also fkine, tr2diff, jacob0, ikine560
- **References** S. Chieaverini, L. Sciavicco, and B. Siciliano, "Control of robotic systems through singularities," in *Proc. Int. Workshop on Nonlinear and Adaptive Control: Issues in Robotics* (C. C. de Wit, ed.), Springer-Verlag, 1991.

ikine560

Purpose Inverse manipulator kinematics for Puma 560 like arm

Synopsis q = ikine560(dh, config)

Description ikine560() returns the joint coordinates corresponding to the end-effector homogeneous transform T. It is computed using a symbolic solution appropriate for Puma 560 like robots, that is, all revolute 6DOF arms, with a spherical wrist. The use of a symbolic solution means that it executes over 50 times faster than ikine() for a Puma 560 solution.

A further advantage is that ikine560() allows control over the specific solution returned. config is a 3-element vector whose values are:

config(1)	-1 or '1'	left-handed (lefty) solution
	1 or 'u'	†right-handed (righty) solution
config(2)	-1 or 'u'	†elbow up solution
	1 or 'd'	elbow down solution
config(3)	-1 or 'f'	†wrist flipped solution
	1 or 'n'	wrist not flipped solution

Cautionary Note that the dimensional units used for the last column of the T matrix must agree with the dimensional units used in the dh matrix. These units can be whatever you choose (metres, inches, cubits or furlongs) but they must be consistent. The Toolbox definitions puma560 and stanford all use SI units with dimensions in metres.

See Also fkine, ikine

References R. P. Paul and H. Zhang, "Computationally efficient kinematics for manipulators with spherical wrists," *Int. J. Robot. Res.*, vol. 5, no. 2, pp. 32–44, 1986.

Author Robert Biro and Gary McMurray, Georgia Institute of Technology, gt2231a@acmex.gatech.edu

inertia

Purpose	Compute the manipulator joint-space inertia matrix
Synopsis	M = inertia(dyn, q)
Description	inertia computes the joint-space inertia matrix which relates joint torque to joint acceleration
	$\underline{\tau} = \mathbf{M}(\underline{q}) \underline{\ddot{q}}$
	dyn describes the manipulator dynamics and kinematics, and q is an n-element vector of joint state.
	For an n-axis manipulator M is an $n \times n$ symmetric matrix.
	Note that if the dyn contains motor inertia parameters then motor inertia, referred to the link reference frame, will be added to the diagonal of M .
Example	To show how the inertia 'seen' by the waist joint varies as a function of joint angles 2 and 3 the following code could be used.
	<pre>>> [q2,q3] = meshgrid(-pi:0.2:pi, -pi:0.2:pi); >> qq = [zeros(length(q2(:)),1) q2(:) q3(:) zeros(length(q2(:)),3)]; >> I11 = []; >> for q=qq' >> I = inertia(p560, q'); >> I11 = [I11; I(1,1)]; >> end >> surfl(q2, q3, reshape(I11, size(q2)));</pre>

Robotics Toolbox Release 4

inertia



- See Also dyn, rne, itorque, coriolis, gravload
- **References** M. W. Walker and D. E. Orin. Efficient dynamic computer simulation of robotic mechanisms. ASME Journal of Dynamic Systems, Measurement and Control, 104:205–211, 1982.

ishomog

Purpose	Test if argument is a homogeneous transformation
Synopsis	ishomog(x)

Description Returns true if x is a 4×4 matrix.

itorque

Purpose	Compute the manipulator inertia torque component
Synopsis	tau_i = itorque(dyn, q, qdd)
Description	itorque returns the joint torque due to inertia at the specified pose q and acceleration qdd which is given by $\underline{\tau}_i = \mathbf{M}(\underline{q}) \underline{\ddot{q}}$
	If q and qdd are row vectors, itorque is a row vector of joint torques. If q and qdd are matrices, each row is interpreted as a joint state vector, and itorque is a matrix in which each row is the inertia torque for the corresponding rows of q and qdd.
	Note that if the dyn contains motor inertia parameters then motor inertia, referred to the link reference frame, will be added to the diagonal of M and influence the inertia torque result.
See Also	dyn, rne, coriolis, inertia, gravload

jacob0

Purpose	Compute manipulator Jacobian in base coordinates
Synopsis	jacob0(dh, q) jacob0(dh, q, M)
Description	jacob0 returns a Jacobian matrix for the current pose q expressed in the base coordinate frame.
	The manipulator Jacobian matrix, ${}^{0}\mathbf{J}_{q}$, maps differential velocities in joint space to Cartesian velocity of the end-effector expressed in the base coordinate frame.
	${}^{\mathrm{o}}\underline{\dot{x}} = {}^{\mathrm{o}}\mathbf{J}_{q}(\underline{q})\underline{\dot{q}}$
	For the case of a manipulator with fewer than 6 DOF the task space cannot include all Cartesian DOF. The 6-element weighting vector, M , whose elements are 0 for those Cartesian DOF that belong to the task space, and 1 otherwise. The elements correspond to translation along the X-, Y- and Z-axes and rotation about the X-, Y- and Z-axes. For example, a 5-axis manipulator may be incapable of independently controlling rotation about the end-effector's Z-axis for which $M = [1 \ 1 \ 1 \ 1 \ 0]$.
	For an n-axis manipulator the Jacobian is a $m \times n$ matrix.
See Also	jacobn, diff2tr, tr2diff, diff
References	R. P. Paul. Robot Manipulators: Mathematics, Programming, and Control. MIT Press, Cambridge, Massachusetts, 1981.

jacobn

Purpose	Compute manipulator Jacobian in end-effector coordinates
Synopsis	jacobn(dh, q) jacobn(dh, q, M)
Description	jacobn returns a Jacobian matrix for the current pose q expressed in the end-effector coordinate frame.
	The manipulator Jacobian matrix, ${}^{0}\mathbf{J}_{q}$, maps differential velocities in joint space to Cartesian velocity of the end-effector expressed in the end-effector coordinate frame.
	${}^{n}\underline{\dot{x}}={}^{n}\mathbf{J}_{q}(\underline{q})\underline{\dot{q}}$
	For the case of a manipulator with fewer than 6 DOF the task space cannot include all Cartesian DOF. The 6-element weighting vector, M , whose elements are 0 for those Cartesian DOF that belong to the task space, and 1 otherwise. The elements correspond to translation along the X-, Y- and Z-axes and rotation about the X-, Y- and Z-axes. For example, a 5-axis manipulator may be incapable of independently controlling rotation about the end-effector's Z-axis for which $M = [1 \ 1 \ 1 \ 1 \ 0]$.
	For an n-axis manipulator the Jacobian is a $m \times n$ matrix.
See Also	jacob0, diff2tr, tr2diff, diff
References	R. P. Paul. Robot Manipulators: Mathematics, Programming, and Control. MIT Press, Cambridge, Massachusetts, 1981.

jtraj

Purpose	Compute a joint space trajectory between two joint coordinate poses
Synopsis	<pre>[q qd qdd] = jtraj(q0, q1, n) [q qd qdd] = jtraj(q0, q1, n, qd0, qd1) [q qd qdd] = jtraj(q0, q1, t) [q qd qdd] = jtraj(q0, q1, t, qd0, qd1)</pre>
Description	jtraj returns a joint space trajectory q from joint coordinates q0 to q1. The number of points is n or the length of the given time vector t. A 7th order polynomial is used with default zero boundary conditions for velocity and acceleration.
	Non-zero boundary velocities can be optionally specified as qd0 and qd1.
	The trajectory is a matrix, with one row per time step, and one column per joint. The function can optionally return a velocity and acceleration trajectories as qd and qdd respectively.

linktran

Purpose	Compute the link transform from kinematic parameters
Synopsis	T = linktran(alpha, a, theta, d) T = linktran(dh, q)
Description	linktrans computes the homogeneous transform between adjacent link coordinate frames based on the standard Denavit-Hartenberg parameters. In the second case, q is substituted on a row-by-row basis for θ_i or D_i according to σ_i .
Algorithm	The homogeneous transform $i^{-1}\mathbf{A}_{i} = \begin{bmatrix} \cos \theta_{i} & -\sin \theta_{i} \cos \alpha_{i} & \sin \theta_{i} \sin \alpha_{i} & a_{i} \cos \theta_{i} \\ \sin \theta_{i} & \cos \theta_{i} \cos \alpha_{i} & -\cos \theta_{i} \sin \alpha_{i} & a_{i} \sin \theta_{i} \\ 0 & \sin \alpha_{i} & \cos \alpha_{i} & d_{i} \\ 0 & 0 & 0 & 1 \end{bmatrix}$ represents each link's coordinate frame with respect to the previous link's coordinate system.
See Also	mlinktran
References	R. P. Paul. Robot Manipulators: Mathematics, Programming, and Control. MIT Press, Cambridge, Massachusetts, 1981.

maniplty

Purpose	Manipulability measure
Synopsis	<pre>m = maniplty(dh, q) m = maniplty(dh, q, M) m = maniplty(dyn, q) m = maniplty(dyn, q, M)</pre>
Description	maniplty computes the scalar manipulability index for the manipulator at the given pose. Manipulability varies from 0 (bad) to 1 (good). The first case, based purely on kinematic data, returns Yoshikawa's manipulability measure which gives an indication of how 'far' the manipulator is from singularities and thus able to move and exert forces uniformly in all directions. The second case, utilizing manipulator dynamic data, returns Asada's manipulability measure which is based on how close the inertia ellipsoid is to spherical.
	If q is a vector maniplty returns a scalar manipulability index. If q is a matrix maniplty returns a column vector and each row is the manipulability index for the pose specified by the corresponding row of q.
	For the case of a manipulator with fewer than 6 DOF the task space cannot include all Cartesian DOF. The 6-element weighting vector, M, whose elements are 0 for those Cartesian DOF that belong to the task space, and 1 otherwise. The elements correspond to translation along the X-, Y- and Z-axes and rotation about the X-, Y- and Z-axes. For example, a 5-axis manipulator may be incapable of independently controlling rotation about the end-effector's Z-axis for which $M = [1 \ 1 \ 1 \ 1 \ 0]$.
Algorithm	Yoshikawa's measure is based on the condition number of the manipulator Jacobian
	$\eta_{yoshi}=\sqrt{ {f J}({f q}){f J}({f q})' }$
	Asada's measure is computed from the Cartesian inertia matrix
	$\mathbf{M}(\underline{x}) = \mathbf{J}(\underline{q})^{-T} \mathbf{M}(\underline{q}) \mathbf{J}(\underline{q})^{-1}$

The Cartesian manipulator inertia ellipsoid is

 $\underline{x}'\mathbf{M}(\underline{x})\underline{x} = 1$

and gives an indication of how well the manipulator can accelerate in each of the Cartesian directions. The scalar measure computed here is the ratio of the smallest/largest ellipsoid axes

 $\eta_{asada} = \frac{\min x}{\max x}$

Ideally the ellipsoid would be spherical, giving a ratio of 1, but in practice will be less than 1.

See Also jacob0, inertia

References T. Yoshikawa, "Analysis and control of robot manipulators with redundancy," in *Proc. 1st* Int. Symp. Robotics Research, (Bretton Woods, NH), pp. 735-747, 1983.

mdh

Purpose	Matrix representati	on of man	ipulator kinematics (modified DH parameters)
Description	A mdh matrix descr Denavit-Hartenberg columns are assigne	ibes the kin conventiced accordin	nematics of a manipulator in a general way using the modified ons. Each row represents one link of the manipulator and the ag to the following table.
	Column	\mathbf{Symbol}	Description
	1	α_{i-1}	link twist angle
	2	A_{i-1}	link length
	3	$ heta_{i}$	link rotation angle
	4	D_i	link offset distance
	5	σ_i	joint type; 0 for revolute, non-zero for prismatic
	If the last column is For an n-axis manij	not given, pulator md	toolbox functions assume that the manipulator is all-revolute. h is an $n \times 4$ or $n \times 5$ matrix.
	The first 5 columns anywhere that a mo	s of a dyn Ih kinemat	matrix contain the kinematic parameters and maybe used ic matrix is required — the dynamic data is ignored.
See Also	mfkine,mrne,dh,pur	na560akb	
References	J. J. Craig, Introdu	ction to R	obotics. Addison Wesley, second ed., 1989.

mdyn

Purpose Matrix representation of manipulator kinematics and dynamics (modified DH parameters)

Description A mdyn matrix describes the kinematics and dynamics of a manipulator in a general way using the modified Denavit-Hartenberg conventions. Each row represents one link of the manipulator and the columns are assigned according to the following table.

Column	\mathbf{Symbol}	$\operatorname{Description}$
1	α_{i-1}	link twist angle
2	A_{i-1}	link length
3	θ_i	link rotation angle
4	D_i	link offset distance
5	σ	joint type; 0 for revolute, non-zero for prismatic
6	mass	mass of the link
7	гx	link COG with respect to the link coordinate frame
8	гy	
9	rz	
10	Ixx	elements of link inertia tensor about the link COG
11	Iyy	
12	Izz	
13	Ixy	
14	Iyz	
15	Ixz	
16	$J\mathrm{m}$	armature inertia
17	G	reduction gear ratio; joint speed/link speed
18	В	viscous friction, motor referred
19	Tc+	coulomb friction (positive rotation), motor referred
20	Tc-	coulomb friction (negative rotation), motor referred

For an n-axis manipulator, mdyn is an $n \times 20$ matrix. The first 5 columns of a mdyn matrix contain the kinematic parameters and maybe used anywhere that a mdh kinematic matrix is required — the dynamic data is ignored.

All angles are in radians. The choice of all other units is up to the user, and this choice will flow on to the units in which homogeneous transforms, Jacobians, inertias and torques are represented.

See Also mdh

mfkine

Purpose	Forward robot kinematics for serial link manipulator (modified DH parameters)
Synopsis	T = mfkine(mdh, q)
Description	mfkine computes the forward kinematics the joint state q. dh describes the manipulator kinematics in modified Denavit-Hartenberg notation.
	If q is a vector it is interpreted as the generalized joint coordinates, and $mfkine$ returns a homogeneous transformation for the final link of the manipulator. If q is a matrix each row is interpreted as as a joint state vector, and T is a matrix in which each row is the 'flattened' homogeneous transform for the the corresponding row in q. The 'flattened' transform can be restored by
	<pre>Ti = reshape(TC(i,:),4,4) , or Ti = ttg(TC, i)</pre>
See Also	mdh,mlinktran, fkine
References	J. J. Craig. Introduction to Robotics. Addison Wesley, second edition, 1989.

mlinktran

Purpose	Compute a link transformation from kinematic parameters (modified DH parameters)		
Synopsis	T = mlinktran(alpha, an, theta, dn) T = mlinktran(mdh, q)		
Description	mlinktrans computes the homogeneous transform between adjacent link coordinate frames based on the modified Denavit-Hartenberg parameters. In the second case, q is substituted on a row-by-row basis for θ_i or D_i according to σ_i .		
Algorithm	The homogeneous transform $i_{i-1}\mathbf{A}_{i} = \begin{bmatrix} \cos \theta_{i} & -\sin \theta_{i} & 0 & a_{i-1} \\ \sin \theta_{i} \cos \alpha_{i-1} & \cos \theta_{i} \cos \alpha_{i-1} & -\sin \alpha_{i-1} & -d_{i} \sin \alpha_{i-1} \\ \sin \theta_{i} \sin \alpha_{i-1} & \cos \theta_{i} \sin \alpha_{i-1} & \cos \alpha_{i-1} & d_{i} \cos \alpha_{i-1} \\ 0 & 0 & 0 & 1 \end{bmatrix}$ represents each link's coordinate frame with respect to the previous link's coordinate system.		
See Also	mdh, mfkine, linktrans		
References	J. J. Craig. Introduction to Robotics. Addison Wesley, second edition, 1989.		

mrne

Purpose	Compute inverse dynamics via recursive Newton-Euler formulation (modified DH parame- ters)
Synopsis	<pre>tau = mrne(mdyn, q, qd, qdd) tau = mrne(mdyn, [q qd qdd])</pre>
	tau = mrne(mdyn, q, qd, qdd, grav) tau = mrne(mdyn, [q qd qdd], grav)
	tau = mrne(mdyn, q, qd, qdd, grav, fext) tau = mrne(mdyn, [q qd qdd], grav, fext)
Description	mrne computes the equations of motion in an efficient manner, giving joint torque as a function of joint position, velocity and acceleration.
	If q, qd and qdd are row vectors then tau is a row vector of joint torques. If q, qd and qdd are matrices then tau is a matrix in which each row is the joint torque for the corresponding rows of q, qd and qdd.
	Gravity by default acts in the $-Z$ direction, grav = [0 0 9.81] m/s ² , but may be over- ridden by providing a gravity acceleration vector grav = [gx gy gz].
	An external force/moment acting on the end of the manipulator may also be specified by a 6-element vector fext = [Fx Fy Fz Mx My Mz] in the end-effector coordinate frame.
	The torque computed may contain contributions due to armature inertia and joint friction if these are specified in the parameter matrix mdyn.
Algorithm	Computes the joint torque
	$\underline{\tau} = \mathbf{M}(\underline{q})\underline{\ddot{q}} + \mathbf{C}(\underline{q},\underline{\dot{q}})\underline{\dot{q}} + \mathbf{F}(\underline{\dot{q}}) + \mathbf{G}(\underline{q})$
	where \mathbf{M} is the manipulator inertia matrix, \mathbf{C} is the Coriolis and centripetal torque, \mathbf{F} the viscous and Coulomb friction, and \mathbf{G} the gravity load.
	Robotics Toolbox Release 4

mrne

See Also dyn, fdyn, accel, gravload, inertia

Limitations A MEX file is currently only available for Sparc architecture.

References J. Y. S. Luh, M. W. Walker, and R. P. C. Paul. On-line computational scheme for mechanical manipulators. *ASME Journal of Dynamic Systems, Measurement and Control*, 102:69-76, 1980.

oa2tr

Purpose	Convert OA vectors to homogeneous transform
Synopsis	oa2tr(o, a)
Description	oa2tr returns a rotational homogeneous transformation specified in terms of the Cartesian orientation and approach vectors o and a respectively.
Algorithm	$\mathbf{T} = \begin{bmatrix} \frac{\hat{o} \times \hat{a}}{0} & \frac{\hat{o}}{0} & \frac{\hat{a}}{0} & 0\\ 0 & 0 & 0 & 1 \end{bmatrix}$ where $\underline{\hat{o}}$ and $\underline{\hat{a}}$ are unit vectors corresponding to 0 and a respectively.
See Also	rpy2tr, eul2tr

plotbot

Purpose Graphical robot animation

Synopsis plotbot(dh, q) plotbot(dh, q, opt)

Description plotbot displays a graphical representation of the robot given the kinematics information in dh. The robot is represented by a simple stick figure where line segments join the origins of the link coordinate frames. If q is a matrix representing a joint-space trajectory then an animation of the robot motion is shown.



The wrist coordinate frame is shown by 3 short orthogonal line segments which are colored: red (X or normal), green (Y or orientation) and blue (Z or approach).

plotbot

Options are specified by opt which is a string which can contain one or more of the following keys:

1	leave trail, that is, don't erase the robot from the previous time step
w	don't draw the wrist axis coordinate frame
r	repeat mode, run the animation 50 times
bvalue	set the base of the robot at coordinate $[0 \ 0 \ value]$ in the 3D plot

See Also fkine, dh

puma560

- Purpose Load kinematic and dynamic data for a Puma 560 manipulator
- Synopsis puma560

Description Defines the matrix p560 which describes the kinematic and dynamic characteristics of a Unimation Puma 560 manipulator. The kinematic conventions used are as per Paul and Zhang, and all quantities are in standard SI units.

Also defines the joint coordinate vectors qz, qr and qstretch corresponding to the zeroangle, ready and fully extended poses.



Details of coordinate frames used for the Puma 560 shown here in its zero angle pose.

See Also dh, dyn, stanford

References	R. P. Paul and H. Zhang, "Computationally efficient kinematics for manipulators with spherical wrists," Int. J. Robot. Res., vol. 5, no. 2, pp. 32–44, 1986.
	 P. Corke and B. Armstrong-Hélouvry, "A search for consensus among model parameters reported for the PUMA 560 robot," in <i>Proc. IEEE Int. Conf. Robotics and Automation</i>, (San Diego), pp. 1608–1613, May 1994.
	P. Corke and B. Armstrong-Hélouvry, "A meta-study of PUMA 560 dynamics: A critical appraisal of literature data," <i>Robotica</i> , vol. 13, no. 3, pp. 253–258, 1995.
See Also	puma560akb

puma560akb

Purpose	Load kinematic and dynamic data for a Puma 560 manipulator
Synopsis	puma560akb
Description	Defines the matrix p560akb which describes the kinematic and dynamic characteristics of a Unimation Puma 560 manipulator. Craig's modified Denavit-Hartenberg notation is used, with the particular kinematic conventions from Armstrong, Khatib and Burdick. All quantities are in standard SI units.
	Also defines the joint coordinate vectors qz, qr and qstretch corresponding to the zero- angle, ready and fully extended poses.
See Also	dh, dyn, stanford
References	B. Armstrong, O. Khatib, and J. Burdick, "The explicit dynamic model and inertial parameters of the Puma 560 arm," in <i>Proc. IEEE Int. Conf. Robotics and Automation</i> , vol. 1, (Washington, USA), pp. 510–18, 1986.

q2tr

Purpose	Convert unit-quaternion to a homogeneous transform
Synopsis	T = q2tr(Q)
Description	Return the rotational homogeneous transform corresponding to the unit quaternion Q .
See Also	${ m tr}2{ m q}$
References	K. Shoemake, "Animating rotation with quaternion curves.," in <i>Proceedings of ACM SIG-GRAPH</i> , (San Francisco), pp. 245–254, The Singer Company, Link Flight Simulator Division, 1985.

qinterp

Purpose	Interpolate unit-quaternions
Synopsis	QI = qinterp(Q1, Q2, r)
Description	Return a unit-quaternion that interpolates between Q1 and Q2 as r varies between 0 and 1 inclusively. This is a spherical linear interpolation (slerp) that can be interpreted as interpolation along a great circle arc on a sphere.
References	K. Shoemake, "Animating rotation with quaternion curves.," in <i>Proceedings of ACM SIG-GRAPH</i> , (San Francisco), pp. 245–254, The Singer Company, Link Flight Simulator Division, 1985.

qinv

Purpose	Inverse of unit-quaternion
Synopsis	QI = qinv(Q)
Description	Return the inverse of the unit-quaternion Q. The inverse is defined such that $q q^{-1} = 1 \label{eq:qq}$
See Also	qqmul,qvmul
References	K. Shoemake, "Animating rotation with quaternion curves.," in <i>Proceedings of ACM SIG-GRAPH</i> , (San Francisco), pp. 245–254, The Singer Company, Link Flight Simulator Division, 1985.

qnorm

Purpose	Normalize a quaternion
Synopsis	QN = qnorm(Q)
Description	Return a unit-quaternion corresponding to the quaternion Q .

qqmul

Purpose	Multiply quaternions
Synopsis	Q = qqmul(Q1, Q2)
Description	Return the product of quaternions, that is, compound the rotations they each represent.
See Also	qvmul,qinv
References	K. Shoemake, "Animating rotation with quaternion curves.," in <i>Proceedings of ACM SIG-GRAPH</i> , (San Francisco), pp. 245-254, The Singer Company, Link Flight Simulator Division, 1985.

qvmul

Purpose	Rotate a vector by a unit-quaternion
Synopsis	VQ = qvmul(Q, V)
Description	Return a Cartesian vector corresponding to the vector ${\tt V}$ rotated by the unit-quaternion Q.
Algorithm	$q_n = \frac{q}{ q }$
See Also	qqmul
References	K. Shoemake, "Animating rotation with quaternion curves.," in <i>Proceedings of ACM SIG-GRAPH</i> , (San Francisco), pp. 245-254, The Singer Company, Link Flight Simulator Division, 1985.
rne

Purpose Compute inverse dynamics via recursive Newton-Euler formulation Synopsis tau = rne(dyn, q, qd, qdd)tau = rne(dyn, [q qd qdd]) tau = rne(dyn, q, qd, qdd, grav) tau = rne(dyn, [q qd qdd], grav) tau = rne(dyn, q, qd, qdd, grav, fext) tau = rne(dyn, [q qd qdd], grav, fext) Description rne computes the equations of motion in an efficient manner, giving joint torque as a function of joint position, velocity and acceleration. If q, qd and qdd are row vectors then tau is a row vector of joint torques. If q, qd and qdd are matrices then tau is a matrix in which each row is the joint torque for the corresponding rows of q, qd and qdd. Gravity by default acts in the -Z direction, grav = $[0 \ 0 \ 9.81] \text{ m/s}^2$, but may be overridden by providing a gravity acceleration vector grav = [gx gy gz]. An external force/moment acting on the end of the manipulator may also be specified by a 6-element vector fext = [Fx Fy Fz Mx My Mz] in the end-effector coordinate frame. The torque computed may contain contributions due to armature inertia and joint friction if these are specified in the parameter matrix dyn. The MEX file version of this function is around 300 times faster than the M file. Algorithm Coumputes the joint torque $\underline{\tau} = \mathbf{M}(q) \ddot{q} + \mathbf{C}(q, \dot{q}) \dot{q} + \mathbf{F}(\dot{q}) + \mathbf{G}(q)$ where \mathbf{M} is the manipulator inertia matrix, \mathbf{C} is the Coriolis and centripetal torque, \mathbf{F} the viscous and Coulomb friction, and G the gravity load. **Robotics Toolbox Release 4**

r	n	e
•	••	~

- Limitations A MEX file is currently only available for Sparc architecture.
- **References** J. Y. S. Luh, M. W. Walker, and R. P. C. Paul. On-line computational scheme for mechanical manipulators. *ASME Journal of Dynamic Systems, Measurement and Control*, 102:69-76, 1980.

rotvec

Purpose	Rotation about a vector
Synopsis	T = rotvec(v, theta)
Description	rotvec returns a homogeneous transformation representing a rotation of theta radians about the vector \mathbf{v} .
See Also	rotx, roty, rotz

rotx,roty,rotz

Purpose	Rotation about X, Y or Z axis
Synopsis	T = rotx(theta) T = roty(theta) T = rotz(theta)
Description	Return a homogeneous transformation representing a rotation of theta radians about the X, Y or Z axes.
See Also	rotvec

rpy2tr

Purpose	Roll/pitch/yaw angles to homogeneous transform
Synopsis	T = rpy2tr([r p y]) T = rpy2tr(r,p,y)
Description	rpy2tr returns a homogeneous transformation for the specified roll/pitch/yaw angles in radians. These correspond to rotations about the Z, X, Y axes respectively.
See Also	${ m tr2rpy,~eul2tr}$
References	R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

rtdemo

Purpose	Robot Toolbox demonstration
Synopsis	rtdemo
Description	This script provides demonstrations for most functions within the Robotics Toolbox.

stanford

Load kinematic and dynamic data for a Stanford manipulator
stanford
Defines the matrix stan which describes the kinematic and dynamic characteristics of a Stanford manipulator. Specifies armature inertia and gear ratios. All quantities are in standard SI units.
dh, dyn, stanford
 R. Paul, "Modeling, trajectory calculation and servoing of a computer controlled arm," Tech. Rep. AIM-177, Stanford University, Artificial Intelligence Laboratory, 1972. R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

tr2diff

Purpose Convert a homogeneous transform to a differential motion vector

Synopsis d = tr2diff(T) d = tr2diff(T1, T2)

Description The first form of tr2diff returns a 6-element differential motion vector representing the incremental translation and rotation described by the homogeneous transform T. It is assumed that T is of the form

 $\begin{bmatrix} 0 & -\delta_z & \delta_y & d_x \\ \delta_z & 0 & -\delta_x & d_y \\ -\delta_y & \delta_x & 0 & d_z \\ 0 & 0 & 0 & 0 \end{bmatrix}$

The translational elements of d are assigned directly. The rotational elements are computed from the mean of the two values that appear in the skew-symmetric matrix.

The second form of tr2diff returns a 6-element differential motion vector representing the displacement from T1 to T2, that is, T2 - T1.

$$d = \left[\begin{array}{c} \underline{p}_2 - \underline{p}_1 \\ 1/2 \left(\underline{n}_1 \times \underline{n}_2 + \underline{o}_1 \times \underline{o}_2 + \underline{a}_1 \times \underline{a}_2 \right) \end{array} \right]$$

See Also diff2tr, diff

References R. P. Paul, *Robot Manipulators: Mathematics, Programming, and Control.* Cambridge, Massachusetts: MIT Press, 1981.

-

tr2eul

Purpose	Convert a homogeneous transform to Euler angles
Synopsis	[a b c] = tr2eul(T)
Description	tr2eul returns a vector of Euler angles, in radians, corresponding to the rotational part of the homogeneous transform T.
See Also	${ m eul}2{ m tr},~{ m tr}2{ m rpy}$
References	R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

tr2jac

Purpose	Compute a Jacobian to map differential motion between frames
Synopsis	jac = tr2jac(T)
Description	tr2jac returns a 6×6 Jacobian matrix to map differential motions or velocities between frames related by the homogeneous transform T.
	If T represents a homogeneous transformation from frame A to frame B, ${}^{A}\mathbf{T}_{B}$, then
	${}^B\underline{\dot{x}} = {}^B\mathbf{J}_A{}^A\underline{\dot{x}}$
	where ${}^{B}\mathbf{J}_{A}$ is given by tr2jac(T).
See Also	tr2diff, diff2tr, diff
References	R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

tr2q

Purpose	Convert homogeneous transform to a unit-quaternion
Synopsis	Q = tr2q(T)
Description	Return a unit quaternion corresponding to the rotational part of the homogeneous transform T.
See Also	m q2tr
References	J. Funda, "Quaternions and homogeneous transforms in robotics," Master's thesis, University of Pennsylvania, Apr. 1988.

tr2rpy

Purpose	Convert a homogeneous transform to roll/pitch/yaw angles
Synopsis	[a b c] = tr2rpy(T)
Description	tr2rpy returns a vector of roll/pitch/yaw angles, in radians, corresponding to the rota- tional part of the homogeneous transform T.
See Also	rpy2tr, tr2eul
References	R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

transl

Purpose	Translational transformation
Synopsis	T = transl(x, y, z) T = transl(v) v = transl(T) xyz = transl(TC)
Description	transl returns a homogeneous transformation representing a translation expressed as three scalar x, y and z, or a Cartesian vector v.
	The third form returns the translational part of a homogeneous transform as a 3-element column vector.
	The fourth form returns a matrix whose columns are the X, Y and Z columns of the Cartesian trajectory matrix TC.
See Also	ctraj, rotx, roty, rotz, rotvec

trinterp

Purpose	Interpolate homogeneous transforms
Synopsis	T = trinterp(T0, T1, r) T = trinterp(T0, dp, r)
Description	trinterp interpolates between the two homogeneous transforms T0 and T1 as r varies between 0 and 1 inclusively. This is generally used for computing straight line or 'Cartesian' motion.
	The second form uses a drive parameter matrix computed by drivepar which represents the 'difference' between T0 and T1 and may be more efficient when computing many inter- polated points between the same two endpoints.
See Also	ctraj, drivepar
References	R. P. Paul, Robot Manipulators: Mathematics, Programming, and Control. Cambridge, Massachusetts: MIT Press, 1981.

trnorm

Purpose	Normalize a homogeneous transformation
Synopsis	TN = trnorm(T)
Description	Returns a normalized copy of the homogeneous transformation T. Finite word length arithmetic can lead to homogeneous transformations in which the rotational submatrix is not orthogonal, that is, $det(\mathbf{R}) \neq -1$.
Algorithm	Normalization is performed by orthogonalizing the rotation submatrix $\underline{n} = \underline{o} \times \underline{a}$.
See Also	diff2tr, diff
References	J. Funda, "Quaternions and homogeneous transforms in robotics," Master's thesis, University of Pennsylvania, Apr. 1988.

ttg

Purpose	Extract homogeneous transformation from Cartesian trajectory
Synopsis	Ti = ttg(T, i)
Description	Returns the homogeneous transformation Ti from the i'th row of the Cartesian trajectory matrix T. Each row of T is a 'flattened' homogeneous transform.
Algorithm	
	Ti = reshape(TC(i,:),4,4)
See Also	ctraj

unit

Purpose	Unitize a vector
Synopsis	vn = unit(v)
Description	unit returns a unit vector aligned with v.
Algorithm	$\underline{v}_n = \frac{\underline{v}}{ \underline{v} }$